



## Master-Clip PTFE H EL

Article Master No.: 000369

Suction & Blower hose for corrosive media up to +175°C, electroconductive, double-layered



antistatic



electrically  
conductive



hydrolysis  
resistant



microbe  
resistant



compressi-  
ble



very  
flexible



light



moderately  
pressure  
resistant

### Product Details

#### Construction / Material

- Type of construction: spiral hose with clamping profile
- Design of the helix: metal band, formed as a clamping profile
- Material of the helix: steel strip, hot-dip galvanised
- Design of the external spiral: designed as an additional protective profile
- Execution of the wall: multi-layered design
- Design of the inner layer: made of electrically conductive material
- Material of the inner layer: PTFE foil
- Specifications of the inner layer: surface resistance  $R_o < 10^6$  Ohm
- Execution of the external layer: HYPALON® coating
- Material of the outer layer: Polyester fabric

#### Properties

- Specifications of the product: according to TRGS 727 and ATEX 2014/34 EU
- Chemical Properties: good resistance to chemicals, weather-resistant, good UV resistance, good ozone resistance
- Mechanical Properties: compressible approx. 1:4
- Flexibility: very flexible
- Physical Properties: heat-resistant, cold-resistant

- Weight: light
- Pressure Resistance: moderately pressure resistant
- Colour: black

### Operating Temperature

- Temperature Range: -40 - 175
- short-term maximum temperature: peaks to 190 °C

### Delivery Information

- Delivery, type of production: order-related production

### Application Areas

- Areas of application: Automotive, Plant & Mechanical Engineering, Ventilation & Air-conditioning, Chemistry, Surface Technology, Waste Disposal & Cleaning Technology, Plastics

### Customizing Options

- optional item modification (on request): other lengths, other nominal widths, with stainless steel spiral

## Article Variants

Extended Article Number	Article number	Nominal Size (DN) mm	Bending radius* mm	Weight kg/m	Operating pressure bar	Negative pressure bar	Max. Production length m
000369:38:x	000369	38	23	0.50	0.94	0.52	20.00
000369:40:x	000369	40	24	0.50	0.93	0.51	20.00
000369:45:x	000369	45	27	0.50	0.92	0.48	20.00
000369:50:x	000369	50	30	0.50	0.90	0.43	20.00
000369:55:x	000369	55	33	0.50	0.85	0.36	20.00
000369:60:x	000369	60	36	0.60	0.78	0.30	20.00
000369:65:x	000369	65	39	0.70	0.68	0.26	20.00
000369:70:x	000369	70	42	0.70	0.67	0.22	20.00
000369:75:x	000369	75	45	0.80	0.62	0.19	20.00
000369:80:x	000369	80	48	0.80	0.61	0.17	20.00
000369:90:x	000369	90	54	0.90	0.56	0.13	20.00
000369:100:x	000369	100	60	1.00	0.51	0.11	20.00
000369:110:x	000369	110	66	1.10	0.48	0.09	20.00
000369:120:x	000369	120	72	1.10	0.36	0.08	20.00
000369:125:x	000369	125	75	1.20	0.33	0.07	20.00
000369:130:x	000369	130	78	1.20	0.28	0.06	20.00
000369:140:x	000369	140	84	1.30	0.25	0.06	20.00
000369:150:x	000369	150	90	1.30	0.22	0.05	20.00
000369:160:x	000369	160	96	1.30	0.21	0.04	20.00
000369:170:x	000369	170	102	1.40	0.19	0.04	20.00
000369:175:x	000369	175	105	1.40	0.19	0.04	20.00
000369:180:x	000369	180	108	1.40	0.17	0.03	20.00
000369:200:x	000369	200	120	1.60	0.15	0.03	20.00
000369:215:x	000369	215	151	1.80	0.13	0.03	20.00

Extended Article Number	Article number	Nominal Size (DN) mm	Bending radius* mm	Weight kg/m	Operating pressure bar	Negative pressure bar	Max. Production length m
000369:225:x	000369	225	158	2.00	0.12	0.02	20.00
000369:250:x	000369	250	175	2.10	0.10	0.02	20.00
000369:275:x	000369	275	193	2.30	0.08	0.02	20.00
000369:300:x	000369	300	210	2.40	0.07	0.01	20.00
000369:325:x	000369	325	228	2.80	0.06	0.01	20.00
000369:350:x	000369	350	245	3.30	0.06	0.01	20.00
000369:375:x	000369	375	263	3.50	0.05	0.01	20.00
000369:400:x	000369	400	280	3.80	0.05	0.01	15.00
000369:450:x	000369	450	360	4.20	0.05	0.01	15.00
000369:500:x	000369	500	400	4.70	0.04	0.01	15.00
000369:550:x	000369	550	440	5.30	0.04	0.01	10.00
000369:600:x	000369	600	480	5.90	0.04	0.01	10.00
000369:700:x	000369	700	560	6.90	0.03	0.01	10.00
000369:800:x	000369	800	640	7.60	0.02	0.01	8.00
000369:900:x	000369	900	720	8.20	0.02	0.01	8.00

All data refer to a medium and ambient temperature of +20°C.  
Specification of the bending radius related to the inside of the hose bend  
Subject to technical changes and colour deviations

## Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

## Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

## Possible Connection Elements



**Hose connector**  
Sheet steel connector for extending, connecting and joining light to medium-weight hoses



**Hose Reducer, symmetrical**  
Hose reducer for extending, connecting and joining light to medium weight hoses



**Clip-Grip Hose Clamp, screwable**  
Screwable clamp for attaching all hose types from the Master-Clip series to mobile and stationary systems



**Clip-Grip Hose Clamp, screwable, Steel quality W4, stainless steel 1.4301**  
screwable clamp for attaching all hose types from the Master-Clip series to mobile and stationary systems



**Clip-Grip Quick-Fix Clamp**  
Special clamp for attaching all hose types from the Master-Clip series to mobile and stationary units.

### Individual consultation

We offer consultation by  
phone:  
+49 209 97077-112

Product requests via  
[masterflex.de/en](https://www.masterflex.de/en)

### Address Headquarters

Masterflex SE  
Willy-Brandt-Allee 300  
45981 Gelsenkirchen

