



Master-Tube PA-E

Polyamide hose with elastomer components



Product Details

Construction / Material

• Execution of the wall: made of highly abrasion-resistant material, made of a material that is insensitive to stress corrosion cracking, made of a material with high impact strength

Properties

- · Specifications of the product: manufactured with calibrated outer diameter
- Chemical Properties: good resistance to solvents, good resistance to oil, good UV resistance, halogen-free, hydrolysis resistant, plasticiser-free, free from paint wetting impairment substances (LABS)
- Physical Properties: flexible at low temperatures

Operating Temperature

• Temperature Range: -40 - 85

Delivery Information

• Delivery, type of production: inner diameter: 2.0 - 9.0 mm, outer diameter: 4.0 - 12.0 mm

Application Areas

 Areas of application: Agriculture, Automotive, Plant & Mechanical Engineering, Robotics & Automation, Industry, Semiconductor Industry, Aerospace technology, Bulk & Construction, Sea & Rail transport, Chemistry, Surface Technology, Food & Pharma, Waste Disposal & Cleaning Technology, Plastics, Conveying, lifting & feeding technology, Textile, Printing & Paper, Vehicle Construction, Metal & Toolmaking

Customizing Options

• optional item modification (on request): other colours, printable, multiple hose, spiral version, shaped hose, rolls, cut-to-size sections

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

Individual consultation

We offer consultation by phone:

+49 209 97077-112

Product requests via masterflex.de/en

Address Headquarters

Masterflex SE Willy-Brandt-Allee 300 45981 Gelsenkirchen

