

Master-PUR HX Food

Article Master No.: 000160

PU suction and delivery hose, heavy, flexible, food-safe EU10/2011 and FDA



hydrolysis resistant



food approved



microbe resistant



transparent



moderately flexible



heavy



very pressure resistant

Product Details

Construction / Material

- Type of construction: profile extruded hose with metal spiral
- Spiral Design: made from stainless steel wire
- Material of the spiral: stainless steel 1.4310, spring steel
- Execution of the wall: made of pure material, made of specified material, extra reinforced wear zones, extremely abrasion resistant due to specific reinforcement underneath the spiral, wall thickness between the spirals approx. 2.0 mm
- Material of the wall: Polyether Polyurethane
- Specifications of the wall: material complies with food regulations FDA 21 CFR § 177.2600 - 21 CFR § 178.2010, approved for direct food contact of categories A, B, C, D1, D2, E, according to EU Directive 1935/2004, 10/2011 and its latest amending Directives

Properties

- Specifications of the product: according to TRGS 727 and ATEX 2014/34 EU, with grounding on both sides of the spiral for aspirative and pneumatic conveying of non-flammable dusts and bulk materials in zone 22. For conveying gases and liquids with low conductivity in zone 2., manufacturing process according to GMP EC 2023/2006
- Chemical Properties: microbe-resistant, odourless and tasteless, good UV resistance, halogen-free, good resistance to chemicals, good ozone resistance, hydrolysis resistant, plasticiser-free
- Flexibility: moderately flexible

- Weight: heavy
- Pressure Resistance: very pressure resistant
- Colour: transparent
- Other: high vacuum and good pressure resistance

Operating Temperature

- Temperature Range: -40 - 90
- short-term maximum temperature: peaks to 125 °C

Delivery Information

- Delivery, type of production: various nominal widths in standard lengths are available ex-production, individual nominal widths and lengths also ex-stock

Application Areas

- Areas of application: Bulk & Construction, Chemistry, Food & Pharma, Plastics

Customizing Options

- optional item modification (on request): other colours, other lengths, other nominal widths, with customer-specific imprint

Article Variants

Extended Article Number	Article number	Nominal Size (DN) mm	Outer diameter mm	Bending radius* mm	Weight kg/m	Operating pressure bar	Negative pressure bar	Max. Production length m	Stock Lengths m
000160:32:x	000160	32	42	80	0.66	4.85	0.94	20.00	/
000160:40:x	000160	40	50	100	0.83	4.27	0.94	20.00	/
000160:51:x	000160	51	61	125	1.04	4.00	0.94	20.00	10
000160:55:x	000160	55	65	140	1.10	3.75	0.89	20.00	/
000160:60:x	000160	60	70	150	1.20	3.60	0.89	20.00	/
000160:65:x	000160	65	75	165	1.29	3.30	0.89	20.00	/
000160:70:x	000160	70	80	175	1.38	3.15	0.89	20.00	/
000160:76:x	000160	76	87	190	1.61	2.92	0.89	20.00	/
000160:80:x	000160	80	93	200	1.93	2.77	0.89	20.00	/
000160:90:x	000160	90	103	225	2.16	2.40	0.89	20.00	/
000160:102:x	000160	102	115	250	2.60	2.10	0.87	20.00	10
000160:110:x	000160	110	124	275	2.82	1.95	0.87	20.00	/
000160:115:x	000160	115	129	290	2.94	1.80	0.87	20.00	/
000160:120:x	000160	120	134	300	3.07	1.65	0.87	20.00	/
000160:127:x	000160	127	140	315	3.44	1.65	0.87	20.00	/
000160:130:x	000160	130	145	325	3.54	1.65	0.84	20.00	/
000160:152:x	000160	152	167	450	4.13	1.50	0.82	20.00	/
000160:140:x	000160	140	153	350	3.81	1.50	0.83	20.00	/

All data refer to a medium and ambient temperature of +20°C.

Specification of the bending radius related to the inside of the hose bend

Subject to technical changes and colour deviations


Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).


Possible Connection Elements




Combiflex VA Threaded Sockets Food
cast-on VA threaded socket with male thread to DIN ISO 228 for all Master-PUR Food hoses, food-safe EU 10/2011




Master-Grip Double Wire Clamp, screw-fitting
Special clamp for fastening light and medium-weight, right-handed spiral hoses such as Flamex B-se, Flamex B-F se, Master-PUR Trivolution, Master-PUR Food, Master-PVC and Master-SANTO



Combiflex Cast-on PU Fixed Flange Food
fixed flange for all Master-PUR Food hose types, approved for direct food contact EU 10/2011, for counterflanges acc. to DIN 2632 / DIN 2633 / DIN 2673



Combiflex PU Threaded Sockets Food
cast-on PU threaded connector for attaching fittings to Master-PUR Food hoses, approved for direct food contact EU 10/2011, following DIN ISO 228



Combiflex Dairy Fitting Cone Sockets
cast-on tube fitting with groove nut to DIN 11851 for Master-PUR Food hoses, food-safe EU 10/2011

Individual consultation

We offer consultation by phone:
+49 209 97077-112

Product requests via
masterflex.de/en

Address Headquarters

Masterflex SE
Willy-Brandt-Allee 300
45981 Gelsenkirchen

