



Polderflex PVC

Article Master No.: 000446

PVC Suction Hose & Transport Hose, pressure & vacuum proof, cadmium-free, flexible



hydrolysis resistant



microbe resistant



flame retardant



moderately flexible



heavy



very pressure resistant

Product Details

Construction / Material

- Type of construction: profile extruded hose with metal spiral
- Spiral Design: made of steel wire
- Material of the spiral: spring steel
- Execution of the wall: made of specified material, wall thickness between the spirals approx. 3 - 10 mm, depending on DN
- Material of the wall: soft PVC
- Specifications of the wall: approved for direct food contact of categories A, B, C, E, according to EU Directive 1935/2004, 10/2011 and its latest amending Directives

Properties

- Specifications of the product: manufacturing process according to GMP EC 2023/2006
- Chemical Properties: atoxic, physiologically harmless, good resistance to oil, good resistance to alkaline solutions, good resistance to acids
- Flexibility: moderately flexible
- Weight: heavy
- Pressure Resistance: very pressure resistant
- Colour: transparent
- Other: high vacuum and good pressure resistance

Operating Temperature

- Temperature Range: -20 - 70
- short-term maximum temperature: peaks to 80 °C

Delivery Information

- Delivery, type of production: various nominal widths in standard lengths are available ex-production, individual nominal widths and lengths also ex-stock

Application Areas

- Areas of application: Bulk & Construction, Sea & Rail transport, Wood, Chemistry, Food & Pharma, Plastics, Vehicle Construction

Customizing Options

- optional item modification (on request): other lengths, other nominal widths, with customer-specific imprint

Article Variants

| Extended Article Number | Article number | Nominal Size (DN) mm | Outer diameter mm | Bending radius* mm | Weight kg/m | Operating pressure bar | Negative pressure bar | Max. Production length m | Stock Lengths m |
|-------------------------|----------------|----------------------|-------------------|--------------------|-------------|------------------------|-----------------------|--------------------------|-----------------|
| 000446:13:x | 000446 | 13 | 19 | 26 | 0.22 | 9.00 | 0.88 | 50.00 | 50 |
| 000446:16:x | 000446 | 16 | 22 | 32 | 0.27 | 9.00 | 0.88 | 50.00 | / |
| 000446:19:x | 000446 | 19 | 26 | 38 | 0.35 | 8.00 | 0.88 | 50.00 | 50 |
| 000446:20:x | 000446 | 20 | 27 | 40 | 0.34 | 8.00 | 0.88 | 50.00 | 50 |
| 000446:25:x | 000446 | 25 | 33 | 50 | 0.52 | 8.00 | 0.88 | 50.00 | 50 |
| 000446:32:x | 000446 | 32 | 40 | 64 | 0.66 | 8.00 | 0.88 | 50.00 | 30 |
| 000446:38:x | 000446 | 38 | 47 | 76 | 0.80 | 7.00 | 0.88 | 50.00 | 30 |
| 000446:40:x | 000446 | 40 | 50 | 80 | 0.95 | 7.00 | 0.88 | 50.00 | 30 |
| 000446:45:x | 000446 | 45 | 55 | 90 | 1.15 | 6.00 | 0.88 | 50.00 | 30 |
| 000446:51:x | 000446 | 51 | 62 | 102 | 1.35 | 5.00 | 0.88 | 50.00 | 30 |
| 000446:60:x | 000446 | 60 | 72 | 120 | 1.75 | 5.00 | 0.88 | 50.00 | 30 |
| 000446:63:x | 000446 | 63 | 75 | 126 | 1.80 | 5.00 | 0.88 | 50.00 | 50 |
| 000446:76:x | 000446 | 76 | 89 | 152 | 2.30 | 4.00 | 0.88 | 30.00 | 30 |
| 000446:90:x | 000446 | 90 | 104 | 270 | 2.95 | 4.00 | 0.88 | 30.00 | / |
| 000446:102:x | 000446 | 102 | 117 | 306 | 3.75 | 3.00 | 0.88 | 20.00 | / |
| 000446:127:x | 000446 | 127 | 143 | 381 | 4.80 | 3.00 | 0.88 | 15.00 | / |
| 000446:152:x | 000446 | 152 | 170 | 456 | 6.50 | 2.00 | 0.88 | 15.00 | / |

All data refer to a medium and ambient temperature of +20°C.

Specification of the bending radius related to the inside of the hose bend

Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

Possible Connection Elements



Hose connector
Sheet steel connector for extending, connecting and joining light to medium-weight hoses



Hose Reducer, symmetrical
Hose reducer for extending, connecting and joining light to medium weight hoses



Heat Shrink Cuff
Heat shrink sleeve for easy connection and sealing of hoses



Hose Clamp with Worm-Gear
Standard clamp for fastening light hose types to connecting pieces on mobile and stationary installations



Hose Clamp with Worm-Gear, Steel quality W4, stainless steel 1.4301
Standard clamp for fastening light hose types to connecting pieces on mobile and stationary installations



Hose Clamp with Bolts
special clamp for fastening medium and heavy spiral hoses to connection pipes on mobile and stationary units

Individual consultation

We offer consultation by phone:
+49 209 97077-112

Product requests via
[masterflex.de/en](https://www.masterflex.de/en)

Address Headquarters

Masterflex SE
Willy-Brandt-Allee 300
45981 Gelsenkirchen

