



Combiflex Clamp Ring Seal

for clamp connection according to DIN 32676 series A

Product Details

Construction / Material

- Specification of the connection solution: liquid-tight connection
- Design of the sealing ring: made of rubber
- Material of the sealing ring: NBR, material complies with the food regulations of DIN 32676 Series A

Properties

- Chemical Properties: odourless and tasteless, good resistance to chemicals
- Mechanical Properties: excellent tensile and tear strength
- Colour: white

Operating Temperature

- Temperature Range: -25 120
- short-term maximum temperature: peaks to 150 °C

Delivery Information

Application Areas

Customizing Options

Article Variants

| Article number | Outer diameter | DN of the hose | Connection mm | Inner |
|----------------|----------------|----------------|---------------|-------|
| | mm | mm | mm | mm |
| 002462 | 52.7 | 32 | 32 | 32.2 |

Combiflex Clamp Ring Seal 2 / 2

| Article number | Outer diameter mm | DN of the hose mm | Connection mm mm | Inner mm |
|----------------|----------------------|----------------------|---------------------|-------------|
| 002465 | 52,7 | 40 | 40 | 38,2 |
| 002468 | 66,2 | 50 | 50 | 50,2 |
| 002472 | 93,2 | 65 | 65 | 66,2 |
| 002476 | 108,2 | 80 | 80 | 81,2 |
| 002480 | 121,2 | 100 | 100 | 100,2 |
| 002483 | 155,0 | 125 | 125 | 125,2 |
| 002485 | 183,0 | 150 | 150 | 150,2 |

Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

Individual consultation

We offer consultation by phone:

+49 209 97077-112

Address Headquarters

Masterflex SE Willy-Brandt-Allee 300 45981 Gelsenkirchen



Product requests via masterflex.de/en